

(Guidelines for Treating the Shed)
All sheds are to be sealed or treated within 60 days of delivery*

All sheds are sold unfinished and, as any good painter will tell you, **must be caulked** prior to treatment, with a stainable/paintable caulk at any seam that may allow water in, such as **trim over doors, windows, vents, along tops & sides of cornerboards and the vertical overlaps on SmartPanel**. Galvanized nails will bleed a grayish stain on wood sheds, so all nail heads should be wood-puttied before treatment. **To prevent knots from bleeding through your finish, see your paint supplier for a knot sealer such as Binz or Kilz which is available in clear or white, and can be applied over the knots before priming & painting or staining.**

Cedar sheds must be treated outside within 60 days of installation. We recommend using a high quality penetrating oil stain on the outside. (Avoid water-cleanup & solid stains) An exterior varnish may be used on the *interior* walls, but this process is only for cosmetic purposes. Cedar is porous and contains tannins, which can cause "water stains" to appear on the inside as humidity leaches the tannins to the surface. They are harmless, but staining or varnishing the inside will minimize this condition.

Pine sheds and pine trim must be stained or primed & painted on the outside within 60 days of installation. We do not recommend using a clear sealer on pine. Treat the knots, prime all surfaces and use exterior acrylic latex paint for best results.

Shed/Smart Panel siding is pre-primed but must still be painted (not stained) within 60 days on the outside with an exterior acrylic latex base paint, **do not use any oil-based product**. The outside trim is untreated pine and also needs to be treated in the manner of unfinished wood described above for pine sheds.

NOTE: ALL type doors & windows, (with the exception of vinyl), should be painted/stained on all six sides (inside, outside, and all four edges), applying extra to the cut edges. ALL shutters and flower boxes, (with the exception of vinyl), must be removed and sealed on all sides as well as treating the siding behind them.

Floors: Use Acrylic Latex Floor paint only. DO NOT use Thompson's waterseal or any oil-based product.

Vinyl sheds do not require treatment, but may need to be maintained with a vinyl siding cleaner as needed.

All Screen Houses must be treated according to the guidelines above, **inside and out**.

Pressure Treated wood and plywood can and should be treated, after it has dried out for a few weeks.

These are guidelines only! Please check with a professional **paint supplier** for recommendations of painting or staining materials and for proper coverage. *Never* apply treatment to moist wood. Be cautious of "all-in-one" waterproofing products and water-based stains, though they may preserve the wood, they allow weathering.

RE-APPLY ACCORDING TO MANUFACTURER'S RECOMMENDATIONS

Stains need to be applied more frequently than exterior latex, usually yearly, for best results.

Shed Size	Smart Panel	Pine	Cedar	Shed Size	Smart Panel	Pine	Cedar
6x6	1 gal	1 gal	1 gal	10x14	2 gal	2 gal	3-4 gal
6x8	1 gal	1 gal	1 gal	10x16	2 gal	2 gal	4-5 gal
8X8	1 gal	1 gal	1-2 gal	10x18	2 gal	2 gal	5 gal
8X10	1 gal	1 gal	2 gal	10x20	2-3 gal	2-3 gal	5-6 gal
8x12	1-2 gal	1-2 gal	3 gal	12X12	2 gal	2 gal	3-4 gal
8x14	1-2 gal	1-2 gal	3 gal	12X14	2 gal	2 gal	5 gal
8x16	2 gal	2 gal	4 gal	12X16	2-3 gal	2-3 gal	5-6 gal
10x10	1 gal	1 gal	2 gal	12X18	2-3 gal	2-3 gal	5-6 gal
10x12	2 gal	2 gal	3 gal	12X20	3-4 gal	3-4 gal	5-6 gal

***Products delivered between November 1st and February 15th may not allow the new owner time to stain or paint the unit due to the temperature or weather. This will not harm the product in any way. The unit must be painted or stained prior to April 15th and the warranty will remain intact.**

DOOR MAINTENANCE - Please remember to stain or paint both sides and all edges of your door(s) to minimize shrinking and swelling due to weather conditions. It is normal for the doors to shrink and swell; sealing them minimizes any movement.

Due to variations in the weather or slight settling of your shed, the door's gate latch may require periodic adjustment, this is a simple procedure which can be completed in just a couple of minutes

using a Phillips screwdriver. Remove the two screws holding the door block and move it so that the latch bar is centered in the loop, then re-install screws. Leave a 1/4" gap between the door block and the center trim, to allow for swelling.

The newer style T-latches should not need adjustment, but you may need to tighten the inside handle set-screw if it loosens. The hex wrench came with latch.

